


Seventh Edition in SI Units

MECHANICS OF MATERIALS


Ferdinand Beer • E. Russel Johnston, Jr. • John DeWolf • David Mazurek



Seventh Edition in SI Units

MECHANICS OF MATERIALS

Ferdinand Beer • E. Russel Johnston, Jr. • John DeWolf • David Mazurek



Seventh Edition in SI Units

Mechanics of Materials

Ferdinand P. Beer

Late of Lehigh University

E. Russell Johnston, Jr.

Late of University of Connecticut

John T. DeWolf

University of Connecticut

David F. Mazurek

United States Coast Guard Academy

**Mc
Graw
Hill**
Education

Contents

Preface	ix
Guided Tour	xiii
List of Symbols	xv

1 Introduction—Concept of Stress 3

- 1.1 Review of The Methods of Statics 4
- 1.2 Stresses in the Members of a Structure 7
- 1.3 Stress on an Oblique Plane Under Axial Loading 27
- 1.4 Stress Under General Loading Conditions; Components of Stress 28
- 1.5 Design Considerations 31
- Review and Summary 44**

2 Stress and Strain—Axial Loading 55

- 2.1 An Introduction to Stress and Strain 57
- 2.2 Statically Indeterminate Problems 78
- 2.3 Problems Involving Temperature Changes 82
- 2.4 Poisson's Ratio 94
- 2.5 Multiaxial Loading; Generalized Hooke's Law 95
- *2.6 Dilatation and Bulk Modulus 97
- 2.7 Shearing Strain 99
- 2.8 Deformations Under Axial Loading—Relation Between E , ν , and G 102
- *2.9 Stress-Strain Relationships For Fiber-Reinforced Composite Materials 104
- 2.10 Stress and Strain Distribution Under Axial Loading; Saint-Venant's Principle 115
- 2.11 Stress Concentrations 117
- 2.12 Plastic Deformations 119
- *2.13 Residual Stresses 123
- Review and Summary 133**

*Advanced or specialty topics

Contents

Preface	ix
Guided Tour	xiii
List of Symbols	xv

1 Introduction—Concept of Stress 3

- 1.1 Review of The Methods of Statics 4
 - 1.2 Stresses in the Members of a Structure 7
 - 1.3 Stress on an Oblique Plane Under Axial Loading 27
 - 1.4 Stress Under General Loading Conditions; Components of Stress 28
 - 1.5 Design Considerations 31
- Review and Summary 44**

2 Stress and Strain—Axial Loading 55

- 2.1 An Introduction to Stress and Strain 57
 - 2.2 Statically Indeterminate Problems 78
 - 2.3 Problems Involving Temperature Changes 82
 - 2.4 Poisson's Ratio 94
 - 2.5 Multiaxial Loading; Generalized Hooke's Law 95
 - *2.6 Dilatation and Bulk Modulus 97
 - 2.7 Shearing Strain 99
 - 2.8 Deformations Under Axial Loading—Relation Between E , ν , and G 102
 - *2.9 Stress-Strain Relationships For Fiber-Reinforced Composite Materials 104
 - 2.10 Stress and Strain Distribution Under Axial Loading; Saint-Venant's Principle 115
 - 2.11 Stress Concentrations 117
 - 2.12 Plastic Deformations 119
 - *2.13 Residual Stresses 123
- Review and Summary 133**

*Advanced or specialty topics

3 Torsion 147

- 3.1 Circular Shafts in Torsion 150
- 3.2 Angle of Twist in the Elastic Range 167
- 3.3 Statically Indeterminate Shafts 170
- 3.4 Design of Transmission Shafts 185
- 3.5 Stress Concentrations in Circular Shafts 187
- *3.6 Plastic Deformations in Circular Shafts 195
- *3.7 Circular Shafts Made of an Elastoplastic Material 196
- *3.8 Residual Stresses in Circular Shafts 199
- *3.9 Torsion of Noncircular Members 209
- *3.10 Thin-Walled Hollow Shafts 211

Review and Summary 223

4 Pure Bending 237

- 4.1 Symmetric Members in Pure Bending 240
- 4.2 Stresses and Deformations in the Elastic Range 244
- 4.3 Deformations in a Transverse Cross Section 248
- 4.4 Members Made of Composite Materials 259
- 4.5 Stress Concentrations 263
- *4.6 Plastic Deformations 273
- 4.7 Eccentric Axial Loading in a Plane of Symmetry 291
- 4.8 Unsymmetric Bending Analysis 302
- 4.9 General Case of Eccentric Axial Loading Analysis 307
- *4.10 Curved Members 319

Review and Summary 334

5 Analysis and Design of Beams for Bending 345

- 5.1 Shear and Bending-Moment Diagrams 348
- 5.2 Relationships Between Load, Shear, and Bending Moment 360
- 5.3 Design of Prismatic Beams for Bending 371
- *5.4 Singularity Functions Used to Determine Shear and Bending Moment 383
- *5.5 Nonprismatic Beams 396

Review and Summary 407

6 Shearing Stresses in Beams and Thin-Walled Members 417

- 6.1 Horizontal Shearing Stress in Beams 420
- *6.2 Distribution of Stresses in a Narrow Rectangular Beam 426
- 6.3 Longitudinal Shear on a Beam Element of Arbitrary Shape 437
- 6.4 Shearing Stresses in Thin-Walled Members 439
- *6.5 Plastic Deformations 441
- *6.6 Unsymmetric Loading of Thin-Walled Members and Shear Center 454

Review and Summary 467

7 Transformations of Stress and Strain 477

- 7.1 Transformation of Plane Stress 480
- 7.2 Mohr's Circle for Plane Stress 492
- 7.3 General State of Stress 503
- 7.4 Three-Dimensional Analysis of Stress 504
- *7.5 Theories of Failure 507
- 7.6 Stresses in Thin-Walled Pressure Vessels 520
- *7.7 Transformation of Plane Strain 529
- *7.8 Three-Dimensional Analysis of Strain 534
- *7.9 Measurements of Strain; Strain Rosette 538

Review and Summary 546

8 Principal Stresses Under a Given Loading 557

- 8.1 Principal Stresses in a Beam 559
- 8.2 Design of Transmission Shafts 562
- 8.3 Stresses Under Combined Loads 575

Review and Summary 591

9 Deflection of Beams 599

- 9.1 Deformation Under Transverse Loading 602
- 9.2 Statically Indeterminate Beams 611
- *9.3 Singularity Functions to Determine Slope and Deflection 623
- 9.4 Method of Superposition 635
- *9.5 Moment-Area Theorems 649
- *9.6 Moment-Area Theorems Applied to Beams with Unsymmetric Loadings 664
- Review and Summary 679

10 Columns 691

- 10.1 Stability of Structures 692
- *10.2 Eccentric Loading and the Secant Formula 709
- 10.3 Centric Load Design 722
- 10.4 Eccentric Load Design 739
- Review and Summary 750

11 Energy Methods 759

- 11.1 Strain Energy 760
- 11.2 Elastic Strain Energy 763
- 11.3 Strain Energy for a General State of Stress 770
- 11.4 Impact Loads 784
- 11.5 Single Loads 788
- *11.6 Multiple Loads 802
- *11.7 Castigliano's Theorem 804
- *11.8 Deflections by Castigliano's Theorem 806
- *11.9 Statically Indeterminate Structures 810
- Review and Summary 823

Appendices A1

A	Moments of Areas	A2
B	Typical Properties of Selected Materials Used in Engineering	A13
C	Properties of Rolled-Steel Shapes	A17
D	Beam Deflections and Slopes	A29
E	Fundamentals of Engineering Examination	A30

Photo Credits C1

Index ii

Index

A

- Allowable (working) load, 32-33
- Allowable stress, 32-33
- Allowable stress design, 723-728, 739, 751
- Aluminum column design, 726
- American Association of Safety and Highway Officials, 34
- American Concrete Institute, 34
- American Forest and Paper Association, 34, 726
- American Institute of Steel Construction (AISC), 34, 723-724, 728
- American standard beam (S-beam), 424
- Angle of twist
 - elastic range and, 151, 167-170
 - circular shafts, 167-170, 224
 - non-circular shafts, 210
 - torque (τ) and, 151, 167-170
 - tubes (thin-walled hollow shafts), 214
- Anisotropic materials, 64, 134
- Anticlastic curvature, 249, 335
- Area (A)
 - centroid of, A2-A7
 - composite, A4-A7, A11-A12
 - moments of, A2-A12
 - radius of gyration, A8-A10
- Average shearing stress, 11, 45, 422, 468
- Average value of stress, 7, 44
- Axial loading
 - eccentric, 238-239, 291-295, 307-312, 337-338
 - member stresses from, 7-10
 - multiaxial, 95-97, 137
 - oblique plane stresses from, 27-28
 - plane of symmetry with, 291-295, 337
 - pure bending and, 238-239, 291-295, 307-312, 337-338
 - strain energy under, 764, 824
 - stress and strain under, 55-145
 - stress components under, 31
- Axial stresses, 7-10
- Axisymmetry of circular shafts, 151-152

B

- Bauschinger effect, 66
- Beam analysis and design, 344-415
 - bending and, 344-415
 - elastic section modulus (S) for, 347-348, 371-372, 396, 408, 410
 - load and resistance factor design (LRFD), 373
 - nonprismatic beams, 348, 396-401, 410
 - prismatic beams, 371-376, 408
 - relationships between load, shear, and bending moment, 260-368, 408
 - shear and bending moment diagrams for, 348-354, 407-408

- shear and stress distributions, 347-348, 407
- sign convention for, 349
- singularity functions for shear and bending moment, 348, 383-391, 409
- step functions, 395, 409
- transverse loadings, 346-348, 407
- Beam of constant strength, 396, 410
- Beams. *See also* Beam analysis and design;
Cantilever beams
 - boundary conditions, 604, 679
 - cantilever, 604-605
 - deflection of, 598-689
 - longitudinal shear on arbitrary elements, 437-439, 468
 - normal stress in, 558-561, 591
 - overhang, 604
 - plastic deformations, 441-442, 469
 - principal stresses in, 559-561, 591
 - shearing stress in, 558-561, 591
 - shearing stress distribution in, 347-348, 407, 422-431, 468
 - simply supported, 604, 606
 - singularity functions for, 348, 383-391, 409, 623-630, 681-682
 - slopes and deflections of, A29
 - span, 346
 - statically determinate, 346-347, 407
 - statically indeterminate, 347, 600, 611-617, 679-681
 - thin-walled members, 439-466, 469
 - unsymmetric loading of, 454-462, 469
- Bearing stresses, connections with, 12, 45
- Bearing surface, 12, 45
- Bending
 - beam analysis and design for, 344-415
 - couple moment (M), 240-241
 - modulus of rupture (R), 274
 - prismatic members, 237-343
 - pure, 237-343
 - strain energy due to, 766, 824
- Bending moment diagrams
 - beam analysis using, 348-354, 407-408
 - by parts for moment-area theorems, 654-659, 684
 - sign convention for, 349
- Bending moments
 - couples, 240-241
 - pure bending in symmetric members, 240-241, 334
 - relationships with load and shear 260-368, 408
 - singularity functions for, 348, 383-391, 409
- Boundary conditions of beams, 604, 679
- Breaking strength, 60-61
- Bridges, design specifications for, 34
- Brittle materials
 - compression test for, 62
 - concrete, 62, 134
 - cracks, 511
 - maximum-normal-stress criterion, 506

- Mohr's criterion for, 510-511, 549
 - rupture of, 60-62
 - stress and strain transformations, 509-511, 549
 - stress-strain diagram determination of, 60-62, 133
 - tensile test for, 60-61
 - under plane stress, 509-511, 549
- Buckling, 692-694
 - Bulk modulus (k), dilatation and, 97-99, 137

C

- Cantilever beams
 - deflection of, 604-605, 651-653, 684
 - moment-area theorem for, 651-653, 684
 - shearing stresses in, 426-427
- Castigliano's theorem, 804-809, 826
- Center of symmetry, 460
- Centric load design, 722-732, 751
- Centric loading, 9, 45
- Centroid of the area, A2-A7
- Circular shafts
 - angle of twist, 151, 167-170, 224
 - axisymmetry of, 151-152
 - deformations in, 151-153
 - modulus of rupture (R), 196, 225-226
 - plastic deformation in, 195-204, 225-227
 - residual stresses in, 199-204, 226-227
 - shearing strain in, 153, 223
 - stress concentrations in, 187-190, 225
 - stresses in, 150-151, 153-161, 223-224
 - torsion in, 148-204, 223-227
- Coefficient of thermal expansion, 82, 136
- Columns, 690-756
 - allowable stress design, 723-728, 739, 751
 - aluminum, 726
 - buckling, 692-694
 - centric load design, 722-732, 751
 - critical load, 692-694, 750
 - eccentric load design, 739-745, 751
 - eccentric loading, 709-714, 751
 - effective length, 698-706, 750
 - Euler's formula for, 694-702, 750
 - fixed ends, 698-700
 - interaction method, 740-741, 751
 - load and resistance factor design (LRFD), 728
 - pin-ended, 694-697
 - secant formula for, 711-712, 751
 - slenderness ratio, 696, 750
 - stability of structures and, 692-702
 - structural steel, 723-724
 - wood, 726
- Combined loads, principal stresses under, 575-583, 592
- Composite area (A)
 - centroid of, A4-A7
 - moment of inertia and, A11-A12

- Composite materials, 259–262, 335
 moduli of elasticity and, 259–260, 335
 pure bending of members of, 259–262, 335
 transformed section of, 260–335
- Compression test, 62
- Computation error detection, 16
- Concentrated loads, 8, 346
- Concrete
 design specifications for, 34
 stress-strain diagram for, 62, 134
- Connections, bearing stress in, 12
- Constant strength, 348
- Coulomb's criterion, 509
- Couple (bending) moments, 240–241
- Cracks, 511
- Critical load, 692–694, 750
- Critical stress, 696
- Curvature
 analysis of curved members, 319–327, 338
 anticlastic, 249, 335
 pure bending and, 241–244, 319–327,
 334–335, 338
 radius of (ρ), 247, 334, 335
 stresses and, 320–323, 338
 transverse cross section, 248–252
 transverse loading, 238–239, 334
- Cylindrical pressure vessels, stresses in,
 520–522, 549
- D**
- Deflection of beams, 598–689, 790–795,
 806–809
 bending moment and, 600–601
 boundary conditions and, 604, 679
 Castigliano's theorem for, 806–809
 deformation under transverse loading,
 602–610, 679–680
 elastic curve, equation of for, 603–606, 679
 energy methods for, 790–795, 806–809
 flexural rigidity (EI), 603–604, 679
 method of superposition for, 601,
 635–643
 moment-area theorems for, 601–602,
 649–659, 664–674, 682–684
 singularity functions for, 623–630, 681–682
 slope and, 607–608, 623–630, 681–682, A29
 statically determinate, 635–636
 statically indeterminate, 600, 611–617,
 636–637, 679–681
 work-energy method for, 790–795
- Deformation (δ). *See also* Elastic deformation;
 Plastic deformation
 axial loading and, 56–58, 68–69, 102–104,
 119–122, 135, 139
 bending in symmetric members, 241–244
 circular shafts, 151–153, 195–204, 223, 225
 deflection of beams under transverse
 loading, 602–610, 679–680
 elastic behavior and, 68–69, 135
 elastic range stresses and, 244–248, 334
 multiaxial loadings, 95–96
 per unit length, 57–58, 133
 plastic behavior and, 65–67, 135
 pure bending, 241–252
 rectangular parallelepiped, 96
 relationships of E , G , and ν , 102–104, 139
 relative displacement for, 69
- shafts, 148–149, 151–153, 209–218, 223,
 225–227
 strain energy and, 760–762, 823
 transmission shafts, 148–149
 torsion and, 148–149, 151–153, 209–218, 223,
 225–227
- Design considerations
 allowable stress and, 32–33
 allowable stress design, 723–728, 739, 751
 centric load design, 722–732, 751
 columns, 722–745, 751
 eccentric load design, 739–745, 751
 factor of safety, 32–34
 impact loads, 786–787, 725–726
 interaction method, 740–741, 751
 load and resistance factor design (LRFD),
 34, 728
 power (P), 185–186, 225
 specifications for, 34
 stress (σ) and, 31–37
 transmission shafts, 185–187, 225
 ultimate strength, 31–32
 working (allowable) load, 32–33
- Dilatation (e), 98–99, 137
- Dimensionless quantities, 58
- Distributed loads, 346
- Double shear, 12, 45
- Ductile materials
 breaking strength, 60–61
 maximum-distortion-energy criterion, 508
 maximum-shearing-stress criterion,
 507–508
 necking, 60
 percent elongation, 61
 percent reduction in area, 62
 strain-hardening, 61
 stress and strain transformations, 507–508,
 548
 stress-strain diagram determination of,
 59–62, 133–134
 ultimate strength, 60–61
 yield, 59, 134
 yield criteria, 507–508, 548
 yield strength, 60–61, 134
- E**
- Eccentric axial loading
 analysis of, 307–312, 338
 columns, 709–714, 751
 forces of, 238–239
 neutral axis, 292
 plane of symmetry with, 291–295, 337
 pure bending and, 238–239, 291–295,
 307–312, 337–338
 secant formula for, 711–712, 751
- Eccentric load design, 739–745, 751
- Eccentric loading, 8–9, 44. *See also* Eccentric
 axial loading
- Effective length, 698–700, 750
- Elastic behavior, 65–67, 134
 plastic behavior compared to, 65–67
 stress-strain diagrams for, 65–66, 134
- Elastic curve
 equation of, 603–606, 679
 flexural rigidity (EI), 603–604, 679
 load distribution and determination of,
 609–610
- Elastic deformation, 68–69, 135
- Elastic flexural formulas, 245, 334
- Elastic limit, 65, 134
- Elastic range
 angle of twist in, 167–170
 internal torque and, 156
 shearing stresses in, 153–160, 223–224
 stresses and deformation, 244–248, 334
 torsion and, 153–160, 167–170, 223–224
- Elastic section modulus (S)
 beam analysis and design for bending,
 347–348, 371–372, 396, 408, 410
 elastic range and cross section of members,
 246, 335
 nonprismatic beam design, 396, 410
 prismatic beam design, 371–372, 408
- Elastic strain energy, 763–769, 824
- Elastic torsion formulas, 155–156, 223
- Elasticity (E), modulus of, 63–65, 102–104,
 134, 139
 composite material members, 259–260, 335
 Hooke's law and, 63–65, 134
 pure bending and, 259–260, 335
 relationships with G and ν , 102–104, 139
 stress and strain directional relationships,
 65, 134
- Elastoplastic material
 plastic deformation of, 119–122, 139
 pure bending in members, 274–278, 338
 torsion in circular shafts, 196–199, 226
- Elementary work, 761
- Endurance limit, 67–68, 135
- Energy methods, 758–822
 Castigliano's theorem, 804–809, 826
 deflection by, 790–795, 806–809
 elastic strain energy, 763–769, 824
 impact loads, 784–787, 725–726
 multiple loads and, 802–804
 single-loaded members, 788–790, 826
 statically indeterminate structures,
 810–816
 strain energy, 760–775, 823–825
 strain-energy density, 762–763, 823
 work and, 788–795, 802–804, 825
 work-energy method, 790–795
- Engineering materials, properties of,
 A13–A16
- Engineering stress and engineering strain, 62
- Equilibrium equations for problem solutions,
 16, 46
- Euler's formula, 694–702, 750
 fixed-end columns, 698–700
 pin-ended columns, 694–697
- F**
- Factor of safety, 32–34, 46
- Failure
 brittle materials under plane stress,
 509–511, 549
 cracks, 511
 design consideration of, 33
 ductile materials, 507–508, 548
 fracture criteria, 509–511, 549
 stress and strain transformations, 507–511,
 548–549
 theories of, 507–513, 548–549
 yield criteria, 507–508, 548

Fatigue, 67-68, 135
 endurance limit, 67-68, 135
 limit of, 67
 repeated loadings and, 67-68

Fiber-reinforced composite materials, 64-65, 104-108, 134, 139
 Hooke's law for, 64-65, 134
 lamina, 64
 laminate, 64-65, 105
 matrix, 64
 multiaxial loading, 105
 stress-strain relationships for, 104-108, 139

Fillet, stress concentrations in, 117-118, 122

Fixed-end columns, 698-700

Flexural rigidity (EI), 603-604, 679

Force
 internal, 10-12
 shearing stresses and, 10-12
 transverse, 44-45

Fracture criteria for brittle materials, 509-511

Free-body diagrams, 4-6, 16, 45
 problem solutions from, 16, 45
 two-force member stress analysis, 4-6

Fundamentals of Engineering Examination, A30

G

Gauge length, 58-59
 General loading conditions, 28-31

H

Hertz (Hz), 185

Hollow shafts (tubes)
 circular, 154-155, 158-160, 223-224
 thin-walled non-circular, 211-216, 227

Homogeneous materials, 94

Hooke's law
 axial loadings, 63-65, 134
 fiber-reinforced composite materials and, 64-65
 modulus of elasticity (E), 63-65, 134
 modulus of rigidity (G), 100-101, 138
 multiaxial loadings, 95-97, 137
 proportional limit for stress, 64, 134
 shearing stress and strain, 100-101, 138-139

Horsepower (hp), 185, 225

I

Impact loads, 725-726, 784-787
 design for, 725-726, 786-787
 energy from, 725, 784-785

In-plane shearing stress, 484, 547

Inertia, moments of, A8-A12

Interaction method, 740-741, 751

Internal forces, 10-12

Internal torque, 156

Isotropic materials, 64, 94, 134

L

Lamina, 64
 Laminate, 64-65, 105
 Lateral strain, 94-95, 137

Line of action, 8

Load and resistance factor design (LRFD), 34, 46, 373, 728

Load-deformation curve, 57

Loadings. *See also* Torsion
 axial, 7-10, 27-28, 31, 55-145
 beam deflection and, 651-653, 664-667, 684-685
 bending and, 238-239, 346-348
 centric, 9, 44
 columns, 692-694, 709-714, 728, 750-751
 combined, 575-583, 592
 concentrated, 8, 346
 critical, 692-694, 750
 design considerations of, 32-34
 distributed, 346
 eccentric, 8-9, 44, 709-714, 751
 factor of safety, 32-34, 46
 general conditions, 28-31, 46
 impact, 784-787, 725-726
 line of action for, 8
 moment-area theorems and, 651-653, 664-667, 684-685
 multiaxial, 95-97, 137
 plane stress and, 556-597
 relationships with shear and bending moment, 260-368, 408
 repeated, 67-68
 reverse, 66-67
 singularity functions for equivalent open-ended, 385-386, 410
 singularity in, 383
 stress and strain under, 55-145
 stress components under, 29-31
 stresses from, 7-10, 27-28, 44
 symmetric, 651-653, 684
 transverse, 238-239, 346-348
 ultimate, 728
 uniformly distributed, 346
 unsymmetric, 454-462, 469, 664-674, 684-685
 working (allowable), 32-33

Longitudinal shear on arbitrary beam elements, 437-439, 468

M

Macaulay brackets, 384-385, 387

Macroscopic cracks, 511

Matrix, 64

Maximum absolute strain, 244, 334

Maximum absolute stress, 244, 334

Maximum deflection, 666-667, 685

Maximum-distortion-energy criterion, 508

Maximum elastic moment, 275-276, 336

Maximum-normal-stress criterion, 506

Maximum-shearing-stress criterion, 507-508

Members
 axial stress in, 7-10
 bearing stress in, 12
 shearing stress in, 10-12
 two-force diagrams for, 4-6
 stability of, 9

Membrane analogy, 210-211

Microscopic cracks, 511

Modulus

bulk (k), 97-99, 137
 elastic section (S), 246, 335, 347-348, 371-372, 396, 408, 410
 elasticity (E), 63-65, 102-104, 134, 259-260, 335
 relationships of E , G , and ν , 102-104, 139
 resilience (σ_r), 763, 824
 rigidity (G), 100-101, 102-104, 138-139
 rupture (R), 196, 225-226, 274
 toughness (ϵ_u), 762-763, 823
 Young's (E), 63

Mohr's circle

plane strain, 532-534, 550
 plane stress, 492-502, 547

Mohr's criterion for brittle materials, 510-511, 549

Moment-area theorems

bending-moment diagrams by parts, 654-659, 684
 cantilever beams, 651-653, 684
 deflection and, 601-602, 649-659, 664-674, 682-685
 first, 601, 649-650, 682
 general principles of, 649-651, 664
 maximum deflection and, 666-667, 685
 second, 601, 650-651, 683
 statically indeterminate beams, 668-674, 685
 symmetric loadings and, 651-653, 684
 unsymmetric loadings, 664-674, 684-685

Moment of inertia, A8-A12

Moments of areas, A2-A12
 centroid of the area, A2-A7
 composite area, A4-A7, A11-A12
 first, A2-A10
 moment of inertia of, A11-A12
 moment of inertia, A8-A12
 parallel-axis theorem, A10-A11
 radius of gyration, A8-A10
 second, A11-A12

Multiaxial loadings, 95-97, 105, 137
 fiber-reinforced composite materials, 105
 Hooke's law for, 95-97, 137
 principle of superposition for, 96
 rectangular parallelepiped deformation from, 96

Multiple loads, work and energy under, 802-804

N

Neutral axis, 243, 334
 Neutral surface, 242-243, 334

Non-circular shafts, 209-216, 227
 angle of twist, 210
 membrane analogy for, 210-211
 thin-walled (tubes), 211-216, 227
 torsion in, 209-216, 227
 uniform rectangular cross sections, 210, 227

Non-rectangular cross sections, plastic deformation in, 277

Nonprismatic beams
 analysis and design for bending, 348, 396-401, 410
 elastic section modulus (S) for, 396, 410

Normal strain, axial loading and, 57-58, 133

Normal stress

- beams, 558–561, 591
- determination of, 7, 44
- maximum criterion for brittle materials, 506
- strain energy and, 763–767, 824

Numerical accuracy, 16

O

- Oblique parallelepiped deformation, 99–100
- Oblique planes, stresses on from axial loading, 27–28, 46
- Orthotropic materials, 105
- Overhanging beam, 604

P

- Parabolic beam, 424–425
- Parallel-axis theorem, A10–A11
- Parallelepipeds
 - oblique, 99–100
 - rectangular, 96
- Percent elongation, 61
- Percent reduction in area, 62
- Permanent set, 65, 134. *See also* Plastic deformation
- Pin-ended columns, 694–697
- Plane strain, 529–537, 549–550
 - Mohr's circle for, 532–534, 550
 - three-dimensional analysis of, 534–537
 - transformation equations, 529–531, 549
 - transformation of, 529–534, 546–550
- Plane stress, 478–479, 480–506, 546
 - Mohr's circle for, 492–502, 547
 - principal stresses, 482–487, 546
 - state of, 478–479
 - three-dimensional analysis, 504–506
 - transformation equations for, 480–482, 546
 - transformation of, 480–487, 546
- Plastic behavior, 65–67, 134
 - elastic behavior compared to, 65–67
 - permanent set, 65, 134
 - stress-strain diagrams for, 65–66, 134
 - reverse loadings and, 66–67
- Plastic deformation
 - Bauschinger effect, 66
 - beams, 441–440, 469
 - circular shafts, 195–204, 225–227
 - creep, 65
 - elastic behavior and, 65–67, 134
 - elastic limit, 65–66, 134
 - elastoplastic material, 119–122, 139
 - elastoplastic members, 274–278, 336
 - members with single plane of symmetry, 278–279
 - modulus of rupture (R), 196, 225–226, 274
 - non-rectangular cross sections, 277
 - permanent deformation and, 200–201, 226–227
 - permanent set, 65–67, 134
 - pure bending and, 273–285, 336
 - rectangular cross sections, 274–277
 - residual stresses, 122–126, 139, 199–204, 226–227, 279, 336

- reverse loadings and, 66–67
 - single-plane symmetric members, 278–279
 - slip, 65
 - stress and strain under axial loads, 65–67, 119–122, 134, 139
 - stress concentrations and, 122
 - thin-walled members, 440–441, 469
 - torsion and, 195–204, 225–227
- Plastic hinge, 441
- Plastic moment, 275–276, 336
- Polar moment of inertia, A8
- Poisson's ratio (ν), 94–95, 102–104, 137
 - lateral strain and, 94–95, 137
 - relationships with E and G , 102–104, 139
- Power (P) transmitted by shafts, 185–186, 225
- Pressure vessels, 520–524, 549
 - cylindrical, 520–522, 549
 - spherical, 522, 549
 - stresses in, 520–524, 549
 - thin-walled, 520–524, 549
- Principal planes of stress, 482–487, 546
- Principal strains, 523
- Principal stresses, 483, 546, 556–597
 - beams, 559–561, 591
 - combined loads and, 575–583, 592
 - loading and, 556–597
 - plane stress transformation and, 483, 546
 - transmission shaft design for, 562–569, 592
- Prismatic beams, design for bending, 371–376, 408
- Prismatic members, pure bending of, 237–343
- Problems
 - computation error detection, 16
 - equilibrium equations for, 16, 46
 - free-body diagrams for, 16, 45
 - numerical accuracy of, 16
 - Saint-Venant's principle for, 115–117, 139
 - SMART methodology for, 15–16
 - solution, method of, 15–19, 45–46
 - statically equivalent, 115–117
 - statically indeterminate, 78–81, 135–136
 - superposition method for, 79–81
 - temperature changes and, 82–88, 136–137
- Properties of materials, A13–A28
- Proportional limit for stress, 64, 134
- Pure bending, 237–343
 - composite members, 259–262, 335
 - curved members, 319–327, 338
 - deformations from, 241–252
 - eccentric axial loading, 238–239, 291–295, 307–312, 337–338
 - elastic range stresses and deformation, 244–248, 334
 - elastoplastic members, 274–278, 336
 - members with single plane of symmetry, 278–279
 - plastic deformations, 273–285, 336
 - prismatic members, 237–343
 - residual stresses from, 279–280
 - stress concentrations from, 263–267, 336
 - symmetric members in, 240–244, 334
 - transverse cross sections, 248–252
 - transverse loading, 238–239, 334
 - unsymmetric bending analysis, 302–307, 337

R

- Radius of curvature (ρ), 247, 334
- Radius of gyration, A8–A10
- Rectangular cross sections, plastic deformation in, 274–277
- Rectangular parallelepiped deformation, 96
- Redundant reactions, 810
- Relative displacement, 69
- Repeated loadings, fatigue from, 67–68
- Residual stresses
 - circular shafts, 199–204, 226–227
 - permanent deformation and, 200–201, 226–227
 - plastic deformation and, 122–126, 136, 199–204, 226–227, 279
 - pure bending and, 279, 336
 - temperature change and, 124
 - torsion and, 199–204, 226–227
- Resilience (u_r), modulus of, 763, 824
- Resistance factor (ϕ), 728
- Reverse loadings, plastic behavior and, 66–67
- Rigidity (G), modulus of, 100–101, 102–104, 138–139
 - Hooke's law and, 100–101, 138
 - relationships with E and ν , 102–104, 139
 - shearing strain and, 100–101, 138
- Rolled steel shapes, properties of, A17–A28
- Rotation, speed of, 185
- Rupture (R), modulus of, 196, 225–226, 274
- Rupture of brittle materials, 60–62

S

- Saint Venant's criterion, 509
- Saint Venant's principle, 115–117, 139
- Secant formula, 711–712, 751
- Section modulus (S), *see* Elastic section modulus
- Shafts, 147–234
 - circular, 148–204, 223–227
 - deformation of, 148–149, 151–153, 209–218, 223, 225–227
 - hollow (tubes), 154–155, 158–160, 223–224
 - non-circular, 209–216, 227
 - plastic deformation of, 195–204, 225–227
 - residual stresses in, 199–204, 226–227
 - statically indeterminate, 170–176, 225
 - stresses in, 150–151, 153–161, 209–218, 223–224
 - thin-walled hollow (tubes), 211–216, 227
 - torsion in, 147–234
 - transmission, 148–149, 185–187, 225
- Shear
 - double, 12, 45
 - relationships with loads and bending moments, 260–368, 408
 - single, 11, 45
 - ultimate strength in, 32
- Shear center, 419, 455, 469
- Shear diagrams, 348–354, 407–408
 - beam analysis for bending, 348–354, 407–408
 - sign convention for, 349
- Shear flow, 419, 421, 440–441, 468
- Shear moments, singularity functions for, 348, 383–391, 409
- Shearing strain
 - axial loading and, 99–102, 138

- circular shafts, 153, 223
- Hooke's law for, 100-101, 138
- modulus of rigidity (G), 100-101, 138
- oblique parallelepiped deformation, 99-100
- Shearing stresses
 - average, 11, 45, 422, 468
 - beam design for, 417-475
 - beams, distribution of in, 347-348, 407, 422-431, 468
 - bending and, 347-348, 407
 - circular shafts, 153-160, 223
 - components of, 30-31
 - elastic range with, 153-160
 - forces exerted on transverse prismatic beams, 418-419, 467
 - horizontal, 419-426, 467
 - in-plane, 484, 547
 - internal force and, 10-12
 - longitudinal, 437-439, 468
 - maximum criterion for ductile materials, 507-508
 - plastic deformation and, 441-446
 - points of application, 44
 - strain energy due to, 767-769, 824
 - thin-walled member design for, 439-466, 469
 - unsymmetric loading and, 454-462, 469
 - vertical, 418, 467
- Simple structures, analysis and design of, 12-15
- Simply supported beam, 604, 606
- Single-loaded members, work of, 788-790, 826
- Single shear, 11, 45
- Singularity functions
 - application to computer programming, 388
 - beams, 348, 383-391, 409, 623-630, 681-682
 - bending analysis and design using, 348, 383-391, 409
 - equivalent open-ended loadings for, 385-386, 410
 - Macaulay brackets, 384-385, 387
 - shear and bending moments using, 348, 383-391, 409
 - slope and deflection using, 623-630, 681-682
- Singularity in beam loading, 383
- Slenderness ratio, 696, 698, 750
- Slope and deflection
 - beams, 607-608, 623-630, 681-682, A29
 - relationship of, 607-608
 - singularity functions for, 623-630, 681-682
- SMART methodology, 15-16
- Span, 346
- Speed of rotation, 185
- Spherical pressure vessels, stresses in, 522, 549
- Stability
 - critical load, 692-694, 750
 - members, 9
 - structures, 692-702
- Stable system, 692-693
- Statically determinate members
 - beams, 346-347, 407, 635-636, 682
 - deflection and, 635-636, 682
 - method of superposition and, 635-636, 682
- Statically equivalent problems, 115-117
 - Saint-Venant's principle, 115-117
 - uniform distribution of, 116-117
- Statically indeterminate members
 - beams, 347, 600-601, 611-617, 636-637, 668-674, 679-682
 - deflection and, 611-617, 636-637, 668-674, 697, 680-682
 - first degree, 381, 612
 - forces, 56
 - method of superposition and, 636-637, 682
 - moment-area theorems for, 668-674, 685
 - problems, 78-81, 135-136
 - second degree, 381, 612
 - shafts, 170-176, 225
 - stress distribution, 8, 56
- Statically indeterminate structures, 810-816
- Statics
 - free-body diagrams, 4-6
 - review of methods, 4-6
- Steel, design specifications for, 34
- Step functions, 385, 409
- Strain (ϵ). *See also* Stress and strain
 - transformations; Stress and strain under axial loading
 - bending, 244, 334
 - circular shafts, 153, 223
 - engineering, 63
 - lateral, 94-95, 137
 - maximum absolute, 244, 334
 - measurement of, 538-541
 - normal, 57-58, 133
 - plane, 529-537, 549-550
 - Poisson's ratio (ν), 94-95, 102-104, 137
 - shearing, 99-102, 138, 153, 223
 - thermal, 82, 136
 - true, 63
- Strain energy, 760-775, 823-725
 - axial loading and, 764, 824
 - bending and, 766, 824
 - deformation and, 760-762, 823
 - elastic, 763-769, 824
 - general state of stress and, 770-775, 825
 - modulus of resilience and, 763, 824
 - modulus of toughness and, 762-763, 823
 - normal stresses and, 763-767, 824
 - shearing stresses and, 767-769, 824
 - torsion and, 767-768, 825
 - transverse loading and, 769
- Strain-energy density, 762-763, 823
- Strain-hardening, 61
- Strain gages, 480, 538, 547
- Strain rosette, 480, 538, 547
- Stress. *See also* Stress and strain
 - transformations; Stress and strain under axial loading
 - allowable, 32-33
 - applications to analysis and design of simple structures, 12-15
 - average value of, 7, 44
 - axial, 7-10, 31
 - beams, distribution of in, 347-348, 407
 - bearing, 12, 45
 - bending, 244-248, 334, 347-348, 407
 - circular shafts, 150-151, 153-160, 223-224
 - components of, 28-31
 - concept of, 2-53
 - critical, 696
 - curved members, 320-323, 338
 - defined, 7
 - direction of the component, 29
 - design considerations, 31-37
 - elastic range deformation and, 244-248, 334
 - engineering, 63
 - exerted on a surface, 29
 - factor of safety, 32-34, 46
 - general loading conditions, 28-31, 46
 - internal forces and, 10-12
 - load and resistance factor design (LRFD), 34, 46
 - loadings and, 7-10, 27-31
 - maximum absolute, 244, 334
 - method of problem solution, 15-19, 45-46
 - normal, 7, 44
 - oblique planes under axial loading, 27-28, 46
 - plane, 478-479, 480-506, 546
 - proportional limit, 64, 134
 - residual, 122-126, 139
 - shearing, 10-12, 30-31, 44-45, 153-160
 - statically indeterminate distribution of, 8
 - true, 63
 - ultimate strength, 31-32
 - uniaxial, 242
 - uniform, 44
- Stress and strain transformations, 476-555
 - brittle materials, 509-511, 549
 - ductile materials, 507-508, 548
 - failure, theories of, 507-513, 548-549
 - general state of stress, 503-504, 548
 - in-plane shearing stress, 484, 547
 - measurement of strain, 538-541
 - Mohr's circle for, 492-502, 547
 - plane strain, 529-537, 549-550
 - plane stress, 478-479, 480-506, 546
 - states of stress, 478-479
 - thin-walled pressure vessels, 520-524, 549
 - three-dimensional stress analysis, 504-506
 - yield criteria, 479
- Stress and strain under axial loading, 55-145
 - bulk modulus (k), 97-99, 137
 - deformations from, 56-57, 68-69, 102-104, 119-122, 135, 139
 - dilatation, 97-99, 137
 - elastic limit, 65, 134
 - elastic versus plastic behavior, 65-67
 - endurance limit, 67-68, 135
 - fatigue from, 67-68, 135
 - fiber-reinforced composite materials, 64-65, 104-108
 - Hooke's law, 63-65, 95-97, 100-101, 134
 - lateral strain, 94-95, 137
 - modulus of elasticity (E), 63-65, 102-104, 134
 - modulus of rigidity (G), 100-101, 102-104, 138-139
 - multiaxial loadings, 95-97, 137
 - normal strain, 57-58, 133
 - plastic deformation, 65-67, 119-126, 134, 139
 - Poisson's ratio (ν), 94-95, 102-104, 137
 - repeated loadings, 67-68
 - residual stresses, 122-126, 139
 - Saint-Venant's principle, 115-117, 139
 - shearing strain, 99-102, 138
 - statically equivalent problems, 115-117
 - statically indeterminate problems, 78-81, 135-136
 - stress concentrations, 117-118, 122, 139
 - stress-strain diagram, 58-62, 65-67, 133-134
 - temperature change effects on, 82-88, 136-137
 - true stress and true strain, 63
 - uniform distribution of, 116-117

Stress concentrations

- circular shafts, 187-190, 225
- circular stress distribution, 117-118
- discontinuity factor (K), 117-118, 139
- fillets, 117-118, 122
- flat stress distribution, 117-118
- plastic deformations and, 122
- pure bending, 263-267, 336
- torsion and, 187-190, 225

Stress-strain diagrams, 57-62, 65-67, 133-134

- axial loading and, 57-62, 65-67, 133-134
- breaking strength, 60-61
- brittle material determination, 60-61, 133
- compression test for, 62
- ductile material determination, 59-62, 133-134
- gage length of specimen, 58-59
- load-deformation curve, 57
- rupture and, 60-61
- tensile test for, 58-62
- ultimate strength, 60-61
- yield strength, 60-61, 134

Structural steel column design, 723-724

Superposition

- method of for deflection, 601, 635-643, 682
- multiaxial problems, 96-97
- principle of, 96
- statically determinate beams, 635-636, 682
- statically indeterminate beams, 636-637, 682
- statically indeterminate problems, 79-81

Symmetric loadings, moment-area theorems for, 651-653, 684

Symmetric members, 240-244, 334

- bending (couple) moments in, 240-241, 334
- deformation from pure bending, 241-244, 334
- plastic deformation in, 278-279

T

Temperature change

- coefficient of thermal expansion, 82, 136
- plastic deformation and, 124
- problems involving, 82-88, 136-137
- residual stresses and, 124
- stress and strain under axial loads and, 82-88, 124, 136-137
- thermal strain, 82, 136

Tensile test, 58-62

Thermal expansion, coefficient of, 82, 136

Thermal strain, 82, 136

Thin-walled members

- beam design for shearing stresses, 439-466, 469
- non-circular (tubes), 211-216, 227
- plastic deformations in, 440-441, 469
- shear flow, 440-441
- shearing stresses in, 439-466, 469
- unsymmetric loading of, 454-462, 469

Three-dimensional analysis

- strain, 534-537
- stress, 504-506

Timber, design specifications for, 34

Torque (T), 148, 151, 156, 167-170

Torsion, 147-234

- angle of twist, 151, 167-170, 210, 214, 224
- circular shafts, 148-204, 223-227
- elastic range, 153-160, 167-170, 223-224
- elastoplastic materials, 196-199, 226
- hollow shafts (tubes), 154-155, 158-160, 223-224
- modulus of rupture (R), 196, 225-226
- non-circular shafts, 209-216, 227
- plastic deformation and, 195-204, 225-227
- residual stresses from, 199-204, 226-227
- shearing stresses from, 153-160, 167-170, 209-218, 224-227
- strain energy due to, 767-768, 825
- stress concentrations and, 187-190, 225
- stresses in, 150-151, 153-161, 223-224
- thin-walled hollow shafts (tubes), 211-216, 227
- transmission shafts, 148-149, 185-187, 225

Torsion formulas

- elastic range, 155-156, 223
- variable circular cross sections, 188, 225

Toughness (e_R), modulus of, 762-763, 823

Transformed section, 240

Transmission shafts

- deformation of, 148-149
- design of, 185-187, 225, 562-569, 592
- power transmitted by, 185-186, 225
- principle stresses and, 562-569, 592
- speed of rotation of, 185

Transverse cross sections, 248-252

Transverse forces, 44-45

Transverse loading

- beam analysis and design for, 346-348, 407
- concentrated, 346
- deflection of beams under, 602-610, 679-680
- distributed, 346
- pure bending and, 238-239, 334
- shear and stress distributions, 347-348, 407
- strain energy under, 769
- support reactions, 347-348
- uniformly distributed, 346

True stress and true strain, 63

Tubes, 211-216. *See also* Shafts

Two-force member analysis, 4-6

U

Ultimate load, 728

Ultimate strength, 31-32, 60-61

Uniaxial stress, 242

Uniform distribution of stress and strain, 116-117

Uniform stress, 44

Uniformly distributed loads, 346

Unstable system, 692-693

Unsymmetric bending analysis, 302-307, 337

Unsymmetric loading

- beam deflection and, 664-674, 684-685
- maximum deflection and, 666-667, 685
- moment-area theorems for, 664-674, 684-685
- thin-walled members, 454-462, 469

V

Volume change, 97-99, 137

- axial loadings and, 97-99, 137
- bulk modulus (k) for, 97-99, 137
- dilatation, 98-99, 137

von Mises criterion, 508

W

Watts (W), 185, 225

Wide-flange beam (W-beam), 424

Wood column design, 726

Work, 788-795, 802-804, 826

- deflection by, 790-795, 806-809
- energy and, 788-795, 802-804, 826
- multiple loads and, 802-804
- single-loaded members, 788-790, 826

Work-energy method, 790-795

Y

Yield, 59, 134

Yield criteria for ductile materials, 507-508, 548

Yield points, 61

Yield strength, 60-61, 134

Yielding, design consideration of, 33

Young's modulus (E), 63. *See also* Elasticity